

# QUICK DRAW<sup>TM</sup>

## AEROSOL

### MULTI-PURPOSE, NON-MELT, SPRAY-GREASE LUBRICANT

#### DESCRIPTION:

Thick, red, penetrating and lubricating grease. Lithium based formulation sprays thin for maximum penetration and then sets up into a thick grease for long-term friction reduction. Fortified with adhesive agents that keep the lubricant where it is needed most.

#### BENEFITS:

- Non-fluorinated
- Resists throw-off
- Clings to vertical surfaces
- Prevents oxidation and rust
- Water, acid, and detergent resistant
- Performs in temperatures from -51°C to 260°C
- Provides superior adhesive, cohesive, extreme pressure and cushioning properties
- Maximum performance even when subjected to high pressure, vibration, or repeated impact



#### FOR USE ON:

Gears - Autoclaves - Ovens - Dryers - Valves - Pumps - Winches - Conveyors - Chain Drives - Fittings Linkages - Threads - Hinges - Cables - Tools - Rollers - Bushings - Pins - Bearings and many other applications.

#### PERFECT FOR:

Farms, Oil Rigs, Refineries, Bottlers, Dairies, Paper Mills, Lumber Mills, Textile Mills, HVAC Services, Industrial Facilities, Waste Facilities, Cement Plants, Auto and Marine Repair

#### APPLICATION:

Shake well. Remove cap and spray a thin film on surface to be covered. Use the extension tube provided for hard-to-reach places. A thickened grease will start to form within seconds after application, and will be fully cured in 5 to 10 minutes. *NOTE: Test for compatibility on inconspicuous area prior to use on painted or plastic surfaces.*

#### SPECIFICATIONS:

Density @ 25°C (ASTM-D-287) .....	Concentrate 7.76 lbs/gal (0.93 g/mL)
Color .....	Red
Appearance .....	Viscous Spray
Net Weight .....	12 oz.
Odor .....	Petroleum Odor
Health/Flammability/Reactivity .....	2/3/0
Personal Protection .....	B - Safety Glasses and Gloves

# MOMAR<sup>®</sup>

**Momar Australia Pty Ltd**

Telephone: +612 9831 4311 • Fax: +612 9831 2994  
www.momar.com.au