

DESCRIPTION:

High-solids, high-performance formulation produces a water-tight film that eliminates corrosion and reduces unwanted sound and vibration. Fills in minor cracks and voids.

BENEFITS:

- Dries fast
- Paintable after 24 hour cure
- Resists cracking and peeling
- Seals out water to stop leaks fast
- Remains pliable in the cold of winter
- Will not sag, melt, or drip in the summer heat
- Covers up to 20 square feet per can



PROTECTS:

Metal, wood, tin, concrete, plastic, roofing materials, and many other surfaces.

USE ON:

Roof leaks, AC drain pans, flashing, concrete and asphalt cracks, weld joints, gutters and downspouts, duct work, post and wood preservation, vehicle undercarriages, hoses and pvc pipes, overlapping seams, below-grade foundations, window sills, fountains, flat roofs, metal roofs, gravel stops, asphalt shingles, drip edges, granulated roofs, rubberized roofs, and millions of other applications.

APPLICATION:

Shake can vigorously. Clean surface of dirt and rust. Hold can 12 inches from surface. Spray a thin even coat building up desired thickness. Remove over-spray with cloth dampened with Momar's K-Lene or comparable solvent. To prevent clogging of tip, turn can upside down and depress tip for 2 seconds. Wipe tip clean.

SPECIFICATIONS:

Density @ 25°C (ASTM-D-287)	0.87 g/mL
Colour	Black
Appearance	Viscous liquid
Odour	Solvent odour
Health/Flammability/Reactivity.....	1/4/0
Personal Protection.....	X - none required