



BIODEGRADABLE PENETRATING LUBRICANT

Description:

White Lightning is a unique para-synthetic penetrating lubricant. White Lightning is suitable for environmentally sensitive areas due to its ability to do its job while still being biodegradable. Its para-synthetic formula allows it to penetrate rust, corrosion, and moisture quickly and safely to free corroded parts, loosen nuts, and aid in the disassembly of mechanical components. White Lightning also meets FDA regulation 21CFR 178.3570 allowing it to be used on equipment in food processing and packaging plants, bottling plants, etc. in food contact areas.

Benefits:

- Fast penetrating para-synthetic formula
- Biodegradable
- Lubricates and prevents rust and corrosion
- Wide operating temperatures -60°F (-51°C) to 350°F (177°C)
- May be used throughout a food plant
- Dielectric strength of 37,000 volts
- Low VOCs
- Safe on metal and plastic
- Ozone safe

WHITE LIGHTNIN IS FOR USE ON:

- Nuts and Bolts
- Chains and Cables
- Linkages
- Cams
- Bottling Equipment
- Slides
- Pins
- Hinges
- Air Tools
- Any type of Mechanical Device



Application:

White Lightning may be sprayed or poured onto problem area. Allow product to sit for 2-3 minutes to allow for maximum penetration. Reapply as needed.

Specifications:

Appearance	Clear, pale yellow fluid
Biodegradable.....	Yes
ISO Viscosity Grade.....	32
SAE Viscosity Grade.....	10
Density (lb/gal)	7.0 (bulk)
Specific Gravity	0.84 (bulk)
Flash Point (ASTM D-92).....	>450°F (232°C)
Copper Strip Corrosion (ASTM D-130).....	1B

MOMAR®

LUBEST®